DIGITAL PRESSURE GAUGE 3"

PG3000

Pressure Unit Choices Available: psi-Bar-MPa 9V-DC Battery Power with Auto-Off Function Zero Offset LCD Digital Display ISO 9001

The New-Flow DPG3000 Digital Pressure Gauge offers ±0.5% full scale accuracy, while SS316 wetted part provides a variety of applications in media of fluids and gases for the industrial field and the commercial field.

Technical Data

Accuracy: ±0.5% of full scale LCD Display: 30X 14.5cm, with 4 digits Dimension: 3", H11.5 X W4.5cm Operating Temperature: -10 to 60°C Over Pressure: 2 times of F.S.

Process Connections: 1/4" NPT Male, standard

Connection Material: SS316

Multiple Pressure Limit: Psi, Bar, MPa


Response Time: <1 ms Total Error (Typical): ±1.00% LCD Resolution: XX.X1/X.XX1/XXX.1

Pressure Range	Accuracy	Resolution		
		PSI	Bar	MPa
100 PSI	Tpy. ±0.5% F.S.	0.01	0.001	0.01
500 PSI	Tpy. ±0.5% F.S.	0.1	0.01	0.01
1000 PSI	Tpy. ±0.5% F.S.	0.1	0.01	0.1
3000 PSI	Tpy. ±0.5% F.S.	1	0.1	1

Applications

Refrigeration Systems	Gas Dynamics	
Level Systems	Sequencing Control	
Flow System	Control & instrumentation	
Pump	Agriculture	
Cylinder Valve	Car industry	
Water Sprinkling System	Heating, Ventilation, Air Condition (HVAC)	

Dimensions



NEW-FLOW

Ordering Information

DPG3000	Code	Pressure Range		
	1	100psi		
	5	500psi		
	10	1000psi		
	30	3000psi		
		Code	Connection po	rt
		U	1/4"NPT (standard)	
		S	Customized	
			Code	Туре
			А	9V DC Battery
₩	\	V	₩	
DPG3000				Complete Ordering Code

